Voidformer

Data Sheet

ABG VOIDFORMER is an interlocking cellular attenuation and infiltration module for use in Sustainable Drainage Systems (SuDS).
The major application is in storm water attenuation on podium decks and beneath ballasted, hard and soft landscaped, green and blue roof areas.

Paver Properties			
Material		Cellular PP	
Colour	(mm)	Black	
Depth	(mm)	Increments of 50mm starting from 100mm	nominal
Coverage rate		2.78 units per m²	
Percentage void space	(%)	95	nominal
Storage volume	(l)	34 per 100mm depth	nominal
Storage volume	(l/m²)	95 per 100mm depth	nominal
Weight	(kg)	2.1 per 100mm depth	nominal
Weight	(kg/m²)	5.84 per 100mm depth	nominal
Chemical resistance		Excellent	
UV Stability		High	

Product Dimensions	
Product dimensions	600mm x 600mm. Increments of 50mm starting from 100mm.

1 The values given are determined from statistical Interpretation of test results obtained in our laboratories and are subject to tolerances. In line with our policy of continuous improvement the right is reserved to make changes without notice at any time.
2 Final determination of the suitability of any information is the sole responsibility of the user. ABG will be pleased to discuss the use of this or any other product but responsibility for selection of a material and its application in any specific project remains with the user.

ABG LTD
E7 Meltham Mills Road, Meltham, Holmfirth, HD9 4DS • +44(0)1484 852096 • www.abgltd.com
a member of BontexGeo Group